

Moulder Artisane

General Characteristics

Construction:

The rigid frame is composed by two flanks in aluminum (10 mm. thickness) machined and braced.

It is driven by belt and chains.

The particular design of carpet boxes allows a fast change of front and rear belt.

The side covers are painted steel.

The three laminating rolls are nonstick.

Thick wool carpet: 6 mm.

Handling handle are included.

Maintenance :

Scraper easily accessible.

Heavy belt easily removable to let belts being aerated.

Various model of Artisane STAF

	Voltage	Parameter setting	Memorizable programs	Out of gear rear belt	Speed inverter	Sharp ends
Artisane 1	Tri 380 V.	Gravitational gauge	X	X	X	X
Artisane 2	Single phase 220 V.	Gravitational gauge	X	$\mathbf{\vee}$		X
Artisane 3	Single phase 220 V.	Electronic screen	K	$\mathbf{\vee}$	$\mathbf{\vee}$	\checkmark

STAF Artisane 3 specificity :

Shutters able to open as wide as required to create a cone which is allowing to make sharp ends at desired magnitude.





Physical characteristics



Net Weight :	200kg
Packed weight : (palet + cardboard)	230kg
Shipping crate gross weight :	260kg
Dimension packed :	1050x830x840 (mm)

(palet + cardboard)

Shipping crate dimensions: 1100x860x840 (mm)

Electrical characteristics

Voltage :

Engine 380 V. Three phase (Artisane 1) Engine 220 V. Single phase (Artisane 2 & 3)

Power: 0.75kW - 2.2A / 3.8A

Frequency : 50 / 60Hz



Capacity

1500 pcs / hour Artisane 1: accept dough 60% humidity Artisane 2 and 3 : accept dough 80% humidity Sharp ends mode: lengthens of 40 cm maximum

Artisane 2 and 3: Artisane is one of the only moulder in the market that can offer vertical or horizontal shaping on the same machine. The purpose is to find the aspect of hand forming orhorizontal shaping. Some special breads need soft and delicate touch. As only one belt exerts force, dough will be blended most quietly allowing better bread lengthens.

Option

- Stainless steel stands with castors
- Stainless steel covering
- Connexion three phase 230 V. (only Arti1)
- Feeding belt (300 or 500 mm.)
- Motorized output belt
- Shipping crate

Security

Our machines comply with:

- machine directive n° 98/37/CE
- French labour code

STAF SAS - ZI de la Bouchardière - 40 rue de la Tarotte - 41100 NAVEIL - FRANCE

Société par actions simplifiée au capital de 348 480 € Tel : +33(0)2 54 73 60 60 - Fax : +33(0)2 54 73 60 65 - Web : www.staf.net / www.staf-sav.net RC BLOIS B 997 917 521 - SIRET : 997 917 521 00020 - APE : 295 E - TVA : FR 59 997 917 521