

General Characteristics

Construction :

Structure in painted steel

Through fixed by velcrot

Trough with all types of felts :
- Synthetic (standard)
- Linen, cotton, polyamide (option)

Cast iron gear (guaranty large service life)

Double front control

Switchable motor in case of power failure

Maintenance :

Germicidal lamps (optional)

Trough easily removable for dry cleaning and ensure an extension of the lifespan of your equipment.



Evolving model

Our Intermediate proofer are evolving : adding back the cap you can it into large swing intermediate proofer with semi automatic unloading.

Electrical characteristics

Voltage : Moteur mono, Tri 220 V. / 380 V.

Power : 0,25kW - 1,1A (intermediate proofer)
0,75kW - 1,8A (lounge)

Frequency : 50 / 60Hz



Physical characteristics



Net Weight :	270kg - 380kg
Packed weight :	300kg - 410kg
Shipping crate gross weight :	340kg - 450kg
Dimension packed :	1130x800x1810 (mm)
Shipping crate dimensions :	1130x800x1810 (mm)

The option STAF Mod Arti allow to control the machine and manage :

- The cycle : piecemeal, 2 by 2 or clocked at your convenience
- Cleaning cycle (germicidal lamps)
- Recall of your through at any time (ideal if varied production)

Capacity

Reference	Length	Depth	High	Nb troughs	Gutters		Capacity	
					Length	Width	Bread 500gr	Bread 940gr
RP 450	1306	921	973	27	1060	140	216	162
RP 451	1306	1115	973	33	1060	140	264	198
RP 451L	1306	1115	973	26	1060	160	182*	104**
RP 452	1306	1315	973	40	1060	140	320	240
RP 452L	1306	1315	973	32	1060	160	224*	128**
RP 550	1606	921	973	27	1360	140	270	216
RP 551	1606	1115	973	33	1360	140	330	264
RP 551L	1606	1115	973	26	1360	160	234*	130**
RP 552	1606	1315	973	40	1360	140	400	320
RP 552L	1606	1315	973	32	1360	160	288*	160**

Capacity indicated are approximate. Many factors come into play such as kind of dough, resting, moulding, placement ... those informations can change the number of loaf per gutters. *Bread de 100g, **Bread de 945g

Option

- Stainless steel covering
- Connexion Three phases 220 V.
- Folding rounding tray (Felt or polyethylene)
- ModArti (screen for calling any trough at any time)
- Shipping crate

Security

Our machines comply with:

- machine directive n° 98/37/CE
- French labour code



STAF SAS - ZI de la Bouchardière - 40 rue de la Tarotte - 41100 NAVEIL - FRANCE

Société par actions simplifiée au capital de 348 480 €

Tel : +33(0)2 54 73 60 60 - Fax : +33(0)2 54 73 60 65 - Web : www.staf.net / www.staf-sav.net
RC BLOIS B 997 917 521 - SIRET : 997 917 521 00020 - APE : 295 E - TVA : FR 59 997 917 521